

BRAMY PRZESUWNE MOŻLIWE WYMIARY



		SN00Z-1 [MLB x MLH]	SN00Z-2 [MLB x MLH]	SN30Z-1 [MLB x MLH]	SN30Z-2 [MLB x MLH]	SN90Z-1 [MLB x MLH]	SN90Z-2 [MLB x MLH]	SL00-1 [MLB x MLH]	SL00-2 [MLB x MLH]	SL30-1 [MLB x MLH]	SL30-2 [MLB x MLH]
Tylko odporność ogniowa EI		---	---	16000 x 6422 50 m ²	16000 x 6422 50 m ²	8000 x 5000 40 m ²	8000 x 5000 40 m ²	---	---	5800 x 4200 16,27 m ²	5800 x 4200 16,27 m ²
Tylko dymoszczelność	S_a	20820 x 6422 102,4 m ²	20820 x 6422 102,4 m ²	---	---	---	---	6940 x 4920 34,14 m ²	6940 x 4920 34,14 m ²	---	---
	S₂₀₀	6940 x 4920 34,14 m ²	6940 x 4920 34,14 m ²	---	---	---	---	6940 x 4920 34,14 m ²	6940 x 4920 34,14 m ²	---	---
Kombinacja: odporność ogniowa / dymoszczelność	S_a	---	---	16000 x 6422 50 m ²	16000 x 6422 50 m ²	8000 x 5000 40 m ²	8000 x 5000 40 m ²	---	---	5800 x 4200 16,27 m ²	5800 x 4200 16,27 m ²
	S₂₀₀	---	---	6940 x 4920 34,14 m ²	6940 x 4920 34,14 m ²	6940 x 4920 34,14 m ²	6940 x 4920 34,14 m ²	---	---	5800 x 4200 16,27 m ²	5800 x 4200 16,27 m ²

Objaśnienie:

MLB - szerokość w świetle otworu [mm]

MLH - wysokość w świetle otworu [mm]